



TECHNICAL DATA	
Safe working load max.	: 600 kg
Max. permitted wind speed	: 12.5 m/s
Typical GVW	: 32 ton
min. operating weight	: 31.4 ton
Outrigger width and length c/c	
- normal jacking	: 8.0/6.5 m
- one side jacking	: 5.6.2/6.5 m
- narrow jacking	: 3.2/6.5 m
Calculation code	:

TECHNICAL DATA	
Safe working load max.	: 1300 lb
Max. permitted wind speed	: 28 mph
Typical GVW	: 72,000 lb
min. operating weight	: 69,500 lb
Outrigger width and length c/c	
- normal jacking	: 315/256 in
- one side jacking	: 220/256 in
- narrow jacking	: 126/256 in
Calculation code	:

EU

PRELIMINARY

All rights reserved
 This specification may be revised without notice.
 This document, which is our exclusive intellectual property, shall be treated as strictly private and confidential and shall neither be copied nor communicated to any third person without our written consent.
 BRONTO SKYLIFT OY AB
 Tampere Finland

ULOTTUVUUSKAAVIO
 RÄCKVIDSDIAGRAM
 OUTREACH DIAGRAM
 ARBEITSDIAGRAM
 DIAGRAMA DE TRABAJO
 РАБОЧАЯ СХЕМА

SYSTEM Vertex G4	Massa kg Suunnittelija Hyväksyjä	Las RKe	Pun 2016-08-17	Yleistoleranssit Koneistus : SFS4011 Keski Meisto : SFS4012 Levy- ja Hitsustyöt: BBS 2.51
Mittakaava : 225	Arkkikoko A2	Status		

Rev.	Muutosno.	Muutos	Pvm	Muut.

Nimitys
 Ulottumakaavio
 S 70 XR, Levitettävä työkori

BRONTO SKYLIFT
 FINLAND
 This drawing is property of Bronto Skylift. Reproduction prohibited without authorization.

Piirustus nro.
R020152A

Rev.